

## ACCESSORIES FOR GLANDS

### FLAMEPROOF CUM WEATHERPROOF STOPPING PLUGS

Our Stopping Plugs may be used as a means of sealing & stopping unused threaded entries in flameproof enclosures.

THESE PRODUCTS ARE  APPROVED

S. NO.	PROD. CODE	THREAD SIZE
1	HCS 20	M25
2	HCS 25	M32
3	HCS 32	M38
4	HCS 50	M50
5	HCS 75	M63



Material	: Brass as per IS 319 Also available in Al./S.S.
Plating	: Nickel Standard Also available in Chrome.
Threads	: Metric Standard Also available in PG/BSC/NPT/BSP
Sealing Rubber Ring	: Neoprene
Flameproof testing as per	: IS/EC 60079-1:2007
Weatherproof testing as per	: IS/IEC 60529-2001
Test Cert. No.	: CIMFR/TC/P/885
Ingress Protection	: IP-66
Application	: For use in Zone 1 & 2 and in Gas group IIC atmosphere.
Pitch of threads	: 1.5 mm

### TAMPER PROOF STOPPING PLUG

These are used to prevent unauthorized removal.



Material	: Brass as per IS 319 Also available in Al./M.S./S.S.
Plating	: Nickel Standard Also available in Chrome.
Threads	: BSC Standard Also available in PG/Metric/NPT/BSP Sizes : 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3"

### FLAMEPROOF CUM WEATHERPROOF REDUCERS

Our reducers effectively reduce the entry thread diameter of enclosures to accept a gland or fitting with a smaller thread diameter.

THESE PRODUCTS ARE  APPROVED

S. NO.	PROD. CODE	MALE THREAD	FEMALE THREAD
1	HCR 25X20	M25	M20
2	HCR 32X25	M32	M25
3	HCR 38X32	M38	M32
4	HCR 50X38	M50	M38
5	HCR 63X50	M63	M50
6	HCR 75X63	M75	M63



Material	: Brass as per IS 319 Also available in Al./S.S.
Plating	: Nickel Standard Also available in Chrome.
Threads	: Metric Standard Also available in PG/BSC/NPT/BSP
Sealing Rubber Ring	: Neoprene
Flameproof testing as per	: IS/EC 60079-1:2007
Weatherproof testing as per	: IS/IEC 60529-2001
Test Cert. No.	: CIMFR/TC/P/H527
Ingress Protection	: IP-66
Application	: For use in Zone 1 & 2 and in Gas group IIC atmosphere.
Pitch of threads	: 1.5 mm