

ALUMINIUM CABLE GLANDS (BWA & CWA)

MATERIAL : Aluminium Alloy

BWA Al. Cable Glands

APPLICATION : For dry & indoor use with all types of extruded bending cables and are used for aluminum armoured termination.

SIZE : M20 to M63

CWA Al. Cable Glands

APPLICATION : For indoor/outdoor use with all types of extruded bending cable and are used for aluminum armoured termination.

SIZE : M20 to M63



EARTHING TAGS

MATERIAL : Brass, Aluminium or Copper

FEATURES:

- Install between the gland entry and equipment.
- Available in various shapes and in all sizes.
- Ensures earth continuity between the electrical equipment & the gland.
- Can be coated or plated as per Customer Specification.

Metric	Product Code	Size	Product Code
M16	HGA ET-16	M50	HGA ET-50
M20	HGA ET-20	M63	HGA ET-63
M25	HGA ET-25	M75	HGA ET-75
M32	HGA ET-32	M80	HGA ET-80
		M90	HGA ET-90
		M100	HGA ET-100



MARINE USE WATERTIGHT CABLE GLANDS

MATERIAL : Brass

FINISH : Nickel Plated

APPLICATION : Outdoor or indoor for use with all types of braided or unarmoured marine electrical cable fittings.

SIZE RANGE : 3/8" to 3"

Pipe Thread A	Gland ID in mm	Rubber ID C	Locknut OD in mm D	Gland OD in mm L	Total Length	Product Code
PF 3/8"	10	8	28	22	38	HCG-10
PF 1/2"	15	10	31.5	28	42	HCG-15
PF 3/4"	20	13	37	33.5	46	HCG-20
PF 1"	25	15	45	42	52	HCG-25
PF 1 1/4"	30	24	46	49.5	57	HCG-30
PF 1 1/2"	40	30	63	55	65	HCG-35
PF 1 1/2"	40	34	63	55	65	HCG-40
PF 2"	45	38	77	69	73	HCG-45
PF 2"	50	44	77	69	73	HCG-50
PF 2 1/2"	55	48	96	85	83	HCG-55
PF 2 1/2"	60	54	96	85	83	HCG-60
PF 3"	65	60	112	100	95	HCG-65
PF 3"	70	64	112	100	95	HCG-70

