

MECHANICALLY CU. CLADED/COATED GROUNDING ROD

Mechanically cladded Copper coated grounding rod is made when electrolytic grade 99.9% copper tube with wall thickness of 0.25 (250 microns) is cladded to a low carbon steel rod.

Rod Size "S"	Length	Product Code
12	1200 (4 ft)	HCR - 1412
	1800 (6 ft)	HCR - 1418
	2400 (8 ft)	HCR - 1424
14	1200 (4 ft)	HCR - 112
	1800 (6 ft)	HCR - 118
	2400 (8 ft)	HCR - 124
16	1200 (4 ft)	HCR - 312
	1800 (6 ft)	HCR - 318
	2400 (8 ft)	HCR - 324
	3000 (10 ft)	HCR - 330
19	1200 (4 ft)	HCR - 412
	1800 (6 ft)	HCR - 418
	2400 (8 ft)	HCR - 424
	3000 (10 ft)	HCR - 430

This rod can also be supplied with threading & also can be made as per customer specification.

STAINLESS STEEL GROUNDING ROD



"HEX" stainless steel ground rods are used to overcome many of the problems caused by galvanic corrosion which can take place between dissimilar metals buried in close proximity. Other advantages of Stainless Steel rod are that they are highly resistant to corrosion and are much more anodic than Copper.

Diameter		Length		Pkg.	Weight Unit (kg)	Product Code
Inches	mm	ft	m			
5/8"	14.2	5'	1.52	10	2,05	HSS - 145
5/8"	14.2	8'	2.44	10	3,28	HSS - 148 *
5/8"	14.2	10'	3.05	10	4,10	HSS - 1410 *
3/4"	17.2	5'	1.52	5	2,75	HSS - 175
3/4"	17.2	10'	3.05	5	5,50	HSS - 1710 *
1.0"	23.1	10'	3.05	1	10,23	HSS - 2410 *

* These are UL listed Grounding / Earthing Rods as per UL Standard.

GROUNDING ROD ACCESSORIES - UNTHREADED RODS

Couplers

These couplers are used to drive the unthreaded Rods deep and ensure continuous contact for Earthing.

Material : Copper Alloy

Product Code : HERC

P. S.: Specify Rod diameter to be used with.

Driving Head

These are used to drive the unthreaded grounding Rods in the Ground.

Material : High Tensile Steel

Product Code : HDSU

P. S.: Specify Rod diameter to be used with.

→ 'S' ←

